

Vertex S

BACKSHEET MONOCRYSTALLINE MODULE

PRODUCT: TSM-XXXDE09R.08

PRODUCT RANGE: 415-435W

435W

MAXIMUM POWER OUTPUT

0~+5W

BINNING TOLERANCE

21.8%

MAXIMUM EFFICIENCY

25 Years **PRODUCT WARRANTY**
25 Years **POWER WARRANTY**



Small in size, big on power Mono Perc

- Small form factor. Generate a huge amount of energy even in limited space.
- Up to 435W, 21.8% module efficiency with high density interconnect technology
- Multi-busbar technology for better light trapping effect, lower series resistance and improved current collection
- Reduce installation cost with higher power bin and efficiency
- Boost performance in warm weather lower temperature coefficient (-0.34%) and operating temperature




Universal solution for residential and C&I rooftops

- Designed for compatibility with existing mainstream optimizers, inverters and mounting systems
- Perfect size and low weight. Easy for handling. Economy for transporting
- Diverse installation solutions. Flexible for system deployment




High Reliability


- 25 year product warranty
- 25 year performance warranty with lowest degradation;
- Minimized micro-cracks with innovative non-destructive cutting technology
- Mechanical performance up to 6000 Pa positive load and 4000 Pa negative load



Trina Solar's Backsheet Performance Warranty






Comprehensive Products and System Certificates



IEC61215/IEC61730/IEC61701/IEC62716/UL61730
 ISO 9001: Quality Management System
 ISO 14001: Environmental Management System
 ISO14064: Greenhouse Gases Emissions Verification
 ISO45001: Occupational Health and Safety Management System



DIMENSIONS OF PV MODULE(mm)



ELECTRICAL DATA (STC) TSM-XXXDE09R.08(XXX=415-435)

Parameter	415	420	425	430	435
Peak Power Watts-P _{MAX} (Wp)*	415	420	425	430	435
Binning Tolerance-P _{MAX} (W)			0 ~ +5		
Maximum Power Voltage-V _{MPP} (V)	41.7	42.0	42.2	42.3	42.5
Maximum Power Current-I _{MPP} (A)	9.94	10.01	10.08	10.17	10.24
Open Circuit Voltage-V _{OC} (V)	50.0	50.1	50.2	50.3	50.4
Short Circuit Current-I _{SC} (A)	10.55	10.58	10.61	10.64	10.67
Module Efficiency η _m (%)	20.8	21.0	21.3	21.5	21.8

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5. *Measuring tolerance: ±3%.

ELECTRICAL DATA (NOCT)

Parameter	312	317	321	325	329
Maximum Power-P _{MAX} (Wp)	312	317	321	325	329
Maximum Power Voltage-V _{MPP} (V)	38.7	39.2	39.5	39.7	40.0
Maximum Power Current-I _{MPP} (A)	8.07	8.10	8.13	8.17	8.23
Open Circuit Voltage-V _{OC} (V)	47.1	47.1	47.2	47.4	47.5
Short Circuit Current-I _{SC} (A)	8.50	8.53	8.55	8.60	8.65

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s.

MECHANICAL DATA

Solar Cells	Monocrystalline
No. of cells	144 cells
Module Dimensions	1762×1134×30 mm (69.37×44.65×1.18 inches)
Weight	21.8 kg (48.1 lb)
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant material	EVA/POE
Backsheet	White
Frame	30mm(1.18 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm ² (0.006 inches ²), Portrait: 350/280 mm(13.78/11.02 inches) Length can be customized
Connector	Stabuli MC4 EVO2 / Trina Solar TS4

TEMPERATURE RATINGS

NOCT(Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of P _{MAX}	-0.34%/°C
Temperature Coefficient of V _{OC}	-0.25%/°C
Temperature Coefficient of I _{SC}	0.04%/°C

MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC) 1500V DC (UL)
Max Series Fuse Rating*	20A / 25A

*Default 20A / 25A upon special request

WARRANTY

25 year Product Workmanship Warranty**
25 year Power Warranty
2% first year degradation
0.55% Annual Power Attenuation

PACKAGING CONFIGURATION

Modules per box: 36 pieces
Modules per 40' container: 936 pieces

(**Please refer to Limited Warranty Supplement that applies to the TSM-***DE09R.B5, TSM-***DE09R.08, Products supplied after 1st Aug 2022 and installed within Australia & New Zealand residential rooftop market.)